

SNBC

Extraordinary
Value!

BTP-R580

Thermal Receipt Printer



Front Exit Design Can Free Counter Space –
Printer Can Be Placed Under a Terminal or Under
a Shelf

Professional Spill-Proof Design and Front Paper Exit

The SNBC BTP-R580 thermal receipt printer is ideal for harsh hospitality, QSR and retail environments. Its spill-proof design meets international IPX1 standards for protection of electronic equipment. The front paper exit allows installation in tight spaces and use as a low-cost kiosk printer.

- Print Speed Up to 230mm per Second
- Two Color Print Capable
- Built-In Power Supply
- Serial, Parallel, USB, Ethernet and Wireless WiFi Interface Options
- Stores and Prints Logo Images
- Extraordinary Reliability
- Contains Everything Necessary in the Carton– Including Communications Cable



BTP-R580 Thermal Receipt Printer



Spill-Proof Design is Especially Suitable for Kitchens and Bars



Drop and Print Paper Loading with Built-In Paper Width Selector



Optional Audio/Visual Print Messenger



Includes Everything Necessary in the Carton

Features

Spill-proof front exit design leads the list of features for fast thermal printing receipt printer applications.

- Super Fast 230mm per Second Print Speed
- Everything You Need is in the Box
- Internal Power Supply – No Brick
- Serial, Parallel, USB, Ethernet and Wireless WiFi Interface Boards Available
- Uses the Same Interface Boards as Other SNBC Printers
- Long-Life Auto-Cutter with Selectable Full or Partial Cut Provides 33 ~ 50% Longer Service than Most Competitors' Printers
- Stores/Prints Logo Images
- Prints Watermark
- Two-Color Print
- Drop and Print Paper Loading
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches – Intuitive Keypad Programming
- Large Paper Roll Capacity
- Includes Starter Paper Roll, Paper Width Selector, Communications Cable, Power Supply Cord, Plus a CD-ROM with Drivers, Utilities and User's Manual

Optional Devices / Upgrades

Upgrade your printer with these easy-to-add options:

- Serial, Parallel, USB, Ethernet and Wireless WiFi Interface Boards Are User Interchangeable
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed

Ports and Connectivity

Connections are recessed – no separate cable cover is required.

- A** Internal Power Supply AC Input
- B** Choice of Serial (Shown), Parallel, USB, Ethernet or Wireless WiFi Interface Boards Available
- C** Cash Drawer
- D** Cable Management Clip

All product and company names are trademarks, service marks or registered trademarks of their respective owners. All features and specifications are subject to change without notice.

Specifications

Max. Print Speed –	Mono:	230mm per Second
	Two-Color:	110mm per Second
Printing Method:	Direct Thermal	
Resolution:	203 DPI x 203 DPI	
Characters Per Line –	Font A:	42 (80mm) / 37 (58mm)
	Font B:	56 (80mm) / 49 (58mm)
Characters Size –	Font A:	12 x 24
	Font B:	9 x 17
Paper Roll Type –	Width:	82 / 80 / 57.5mm ± 0.5mm
	Maximum Diameter:	100mm
	Paper Thickness:	0.06mm ~ 0.145mm
	Auto Paper Cutting Method:	Auto-Cutter with Selectable Full or Partial Cut
Reliability –	MTBF:	360,000 Hours
	MCBF:	52,000,000 Lines
	Printhead Life:	150,000,000 Characters
	Cutter Life:	2,000,000 Cuts
Character Set –	Alphanumeric:	95
	International:	13
	Graphic:	128 x 13 Page
Bar Code –	1D:	UPC-A / UPC-E / EAN8 / EAN13 / Code39 / Code93 / CODE128 / CODABAR / ITF
	2D:	PDF417 / QR Code / Maxicode
Interpreter:	ESC/POST™	
Interface:	Serial / Parallel / USB / Ethernet / Wireless WiFi	
Driver –	32 bit:	Win2000
	32 bit & 64 bit:	XP / Server2003 / Server 2008 / VISTA / Win7
	Other:	Linux CUPS / MAC Support / OPOS / JavaPOS
Drawer Port:	2 Port (+24VDC) with Drawer Compulsion	
Data Buffer – Receive Buffer RAM:	4 ~ 64 K, or 45 bytes	
	RAM Bitmap:	12 KB
	Flash Bitmap:	256 KB
Power Supply:	AC 100 ~ 240 V, 50/60 Hz Adapter Included	
Current/Power Usage:	2.5A / 60W	
Operating Temperature:	40° ~ 114°F (5° ~ 45°C)	
Operating Humidity:	20% ~ 90% RH (Non-Condensing)	
Dimensions:	5-3/4"W x 5-3/4"H x 8-1/16"D	
Shipping Weight:	6 lbs.	
Safety and EMI:	FCC / RoHS	

